




Tubular Cable Lugs (BS 4579)



- Electrolytic high conductivity copper
- Electro tinned plated
- With / without inspection hole



Product Ref.	Conductor Size mm ²	Stud Hole	Dimensions mm				
			E	B	W	I	O
CCT-438	1.5	M 4	5.5	8	1.8	3.7	17
CCT-538	1.5	M 5	-	8	-	-	17
CCT-539	1.5	M 6	-	10	-	-	19
CCT-388	2.5	M 4	8	8	2.4	4.0	21.5
CCT-540	2.5	M 5	-	10	-	-	21.5
CCT-436	2.5	M 5	-	8	-	-	21.5
CCT-541	2.5	M 6	-	10	-	-	24
CCT-389	4	M 5	8	10	3.1	4.8	21
CCT-543	4	M 6	-	10	-	-	21
CCT-404	4	M 5	-	9	-	-	21
CCT-424	4	M 8	-	12	-	-	26.5
CCT-390	6	M 5	10	10	3.8	5.5	23
CCT-444	6	M 6	-	10	-	-	23
CCT-544	6	M 6	-	12	-	-	27
CCT-545	6	M 8	-	12	-	-	27
CCT-423	6	M 10	-	16.8	-	-	32
CCT-405	10	M 5	10	12	4.5	6.2	25.5
CCT-353	10	M 6	-	12	-	-	25.5
CCT-547	10	M 8	-	12	-	-	27.5
CCT-447	10	M 10	-	19	-	-	32
CCT-430	10	M 12	-	19	-	-	36
CCT-429	16	M 5	13	12	5.4	7.1	31
CCT-354	16	M 6	-	12	-	-	31
CCT-549	16	M 8	-	12	-	-	31
CCT-440	16	M 10	-	19	-	-	35
CCT-401	16	M 12	-	19	-	-	39
CCT-550	20	M 8	13	12	6.0	7.7	32.5
CCT-355	25	M 6	14	13	6.8	8.8	33
CCT-551	25	M 8	-	16	-	-	33
CCT-552	25	M 10	-	16	-	-	36.5
CCT-402	25	M 12	-	18	-	-	40
CCT-542	35	M 6	14	15	8.2	10.6	36
CCT-403	35	M 6	-	15	-	-	38
CCT-356	35	M 8	-	15	-	-	36
CCT-301	35	M 8	-	15	-	-	38
CCT-399	35	M 10	-	15	-	-	40
CTI-544	35	M 10	-	18	-	-	39
CCT-406	35	M 10	-	18	-	-	41
CCT-419	35	M 12	-	20	-	-	42