


**Connectors Non Tension
DIN 46267 Part 1**


- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm ²	Dimensions mm		
		I	O	L
CD 6	6	3.8	5.5	30
CD 10	10	4.5	6	30
CD 16	16	5.5	8.5	50
CD 25	25	7	10	50
CD 35	35	8.2	12.5	50
CD 50	50	10	14.5	56
CD 70	70	11.5	16.5	56
CD 95	95	13.5	19	70
CD 120	120	15.5	21	70
CD 150	150	17	23.5	80
CD 185	185	19	25.5	85
CD 240	240	21.5	29	90
CD 300	300	24.5	32	100
CD 400	400	27.5	38.5	150
CD 500	500	31	42	160
CD 625	625	34.5	44	160
CD 800	800	40	52	200
CD 1000	1000	44	58	200

**Butt Connectors Non Tension
with Barrier: DIN 46267**

- Electrolytic high conductivity copper
- Electro tinned plated
- Leak Proof Against Oil



Product Ref.	Conductor Size mm ²	Dimensions mm		
		I	O	L
CB 16	16	5.5	8.5	50
CB 25	25	7	10	50
CB 35	35	8.2	12.5	50
CB 50	50	10	14.5	56
CB 70	70	11.5	16.5	56
CB 95	95	13.5	19	70
CB 120	120	15.5	21	70
CB 150	150	17	23.5	80
CB 185	185	19	25.5	85
CB 240	240	21.5	29	90
CB 300	300	24.5	32	100
CB 400	400	27.5	38.5	150
CB 500	500	31	42	160
CB 625	625	34.5	44	160