


## Butt Connectors Standard Type


- Electrolytic high conductivity copper
- Electro tinned plated
- With inspection hole



Product Ref.	Conductor Size mm <sup>2</sup>	Dimensions mm		
		I	O	L
BC - 0.75	0.75	1.3	2.8	20
BC - 1.5	1.5	1.8	3.3	25
BC - 2.5	2.5	2.3	4.2	25
BC - 4	4	3	5	25
BC - 6	6	3.5	6.5	25
BC - 10	10	4.5	7	30
BC - 16	16	5.5	8.5	35
BC - 25	25	7	10	40
BC - 35	35	8.5	12	45
BC - 50	50	10	14	50
BC - 70	70	12	16.5	55
BC - 95	95	13.5	18	60
BC - 120	120	15	19.5	65
BC - 150	150	16.5	21	70
BC - 185	185	19	24	75
BC - 240	240	21	26	85
BC - 300	300	23.5	29.5	100
BC - 400	400	27	34	100

## Butt Connectors Standard Type For Solid Conductors

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm <sup>2</sup>	Wire	Dimensions mm		
			I	O	L
BS - 1.5 / 2.5	1.5 / 2.5	1.38 / 1.78	1.9	3.9	25
BS - 4	4	2.25	2.4	4.4	25
BS - 6	6	2.75	3	5	25
BS - 10	10	3.55	4	6	25
BS - 16	16	4.50	5	8	35
BS - 25	25	5.65	6.2	10	40
BS - 35	35	6.70	7	10	40
BS - 50	50	8.00	8.5	12	70