




**Tubular Cable Connector
MV Series**

- Electrolytic high conductivity copper
- Electro tinned plated
- With inspection hole




Product Ref.	Conduct of Size	Dimensions		
		I	O	L
CMV 25	25	6.8	9	35
CMV 35	35	8.2	11	40
CMV 50	50	9.5	13	45
CMV 70	70	11.2	15	50
CMV 95	95	13.5	17.8	60
CMV 120	120	14.5	19.5	65
CMV 150	150	16.5	22	70
CMV 185	185	18	24	75
CMV 240	240	21	27.5	90
CMV 300	300	24	31	100
CMV 400	400	26.5	35	120
CMV 500	500	29.5	39	130
CMV 630	630	33	43	140
CMV 800	800	39	50.6	180
CMV 1000	1000	43	56.2	180



**Copper Blocked Connector
MV Series**

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref	Dimension			
	I1	I2	O	L
CMVBC 120/120	14.5	14.5	20.5	80
CMVBC 150/120	16.5	14.5	22	90
CMVBC 150/150	16.5	16.5	22	90
CMVBC 185/120	18	14.5	24	100
CMVBC 185/150	18	16.5	24	100
CMVBC 185/185	18	18	24	100
CMVBC 240/120	21.5	14.5	27.5	115
CMVBC 240/150	21.5	16.5	27.5	115
CMVBC 240/185	21.5	18	27.5	115
CMVBC 240/240	21.5	21.5	27.5	115
CMVBC 300/120	24.5	14.5	31	120
CMVBC 300/150	24.5	16.5	31	120
CMVBC 300/185	24.5	18	31	120
CMVBC 300/240	24.5	21.5	31	120
CMVBC 300/300	24.5	24.5	31	120
CMVBC 400/240	26	21.5	37	165
CMVBC 400/300	26	24.5	37	165