


Tubular Cable Lugs Soldering Type (BSS: 91)

- Electrolytic high conductivity copper
- Electro tinned plated




Product Ref.	Conductor Size mm ²	Stud Hole	Dimensions mm								
			E	B	W	E	O	C1	C2	L1	L
ST 15-4.5	15	M4,5	10	9	5.1	6.2	5	6	19	24	1.4
ST 30-6	30	M6	13	12	6.5	8.0	6	10	27	33	1.6
ST 60-10	60	M10	14	17	10.8	11.3	9	13	35	44	1.8
ST 60-8	60	M8	14	17	8.2	11.3	9	13	35	44	1.8
ST 100-10	100	M10	19	21	10.8	13.9	13	14	42	55	2.0
ST 150-12	150	M12	22	25	13	17.1	14	16	48	62	2.8
ST 200-12	200	M12	29	29	13	19.9	17	21	61	78	3.2
ST 300-14	300	M14	32	36	15	24.2	20	21	66	86	3.6
ST 300-10	300	M10	32	36	10.8	24.2	20	21	66	86	3.6
ST 400-14	400	M14	38	41	15	27.8	24	24	76	100	4
ST 500-18	500	M18	44	46	19.5	31.4	27	24	84	111	5.2

Tubular Cable Lugs Soldering Type (BSS: 91)

As per cable size

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm ²	Stud Hole	Dimensions mm								
			E	B	W	E	O	C1	C2	L1	L
ST 6-4.5	6	M 4,5	10	9	5.5	6	5	6	19	24	1.6
ST 16-6	16	M 6	13	11	6.6	8	6	7	25	31	2
ST 25-13	25	M 8	13	14	9	10	10	12	31	41	2.4
ST 35-16	35	M 8	16	17	9	12	10	12	36	46	2.4
ST 70-10	70	M 10	19	23	11	16.6	13	14	42	55	4.6
ST 95-12	95	M 12	22	28	14	19.5	14	16	48	62	5.2
ST 120-12	120	M 12	29	32	14	22.5	18	20	60	78	5.8
ST 185-12	185	M 12	32	40	14	27.8	20	21	66	86	7.2
ST 240-16	240	M 16	38	45	18	31	24	24	76	100	7.2
ST 300-16	300	M 16	44	49	18	34.2	27	24	84	111	8.1
ST 500-20	500	M 20	48	59	22	40.9	30	25	91	121	9.2
ST 625-24	625	M 24	56	67	26	46.1	34	29	105	139	9.6
ST 625	625		56	67	--	46.1	34	29	105	139	9.6