

**Copper Butt Splices
Long Barrel (AWG)**



Product Ref.	Conductor Size	Colour Code	Die Index	Dimensions inches		
				O	I	L
CAS 1000-2	1000 MCM	WHITE	27	1.504	1.170	6.12
CAS 750 -2	750 MCM	BLACK	24	1.302	1.030	5.88
CAS 600 -2	600 MCM	GREEN	22 OR 472	1.185	0.920	5.50
CAS 500 -2	500 MCM	BROWN	20 OR 299	1.064	0.830	4.62
CAS 400 -2	400 MCM	BLUE	19 OR 470	0.953	0.758	4.38
CAS 350 -2	350 MCM	RED	18 OR 324	0.877	0.700	4.13
CAS 300 -2	300 MCM	WHITE	17 OR 298	0.815	0.649	4.13
CAS 250 -2	250 MCM	YELLOW	16	0.753	0.594	3.39
CAS 4/0 -2	4 / 0 STR	PURPLE	15	0.691	0.545	3.39
CAS 3/0 -2	3 / 0 STR	ORANGE	14	0.618	0.487	3.15
CAS 2/0 -2	2 / 0 STR	BLACK	13	0.563	0.446	3.15
CAS 1/0 -2	1 / 0 STR	PINK	12 OR 348	0.515	0.391	2.91
CAS 1 -2	1 STR	GREEN	11 OR 375	0.462	0.354	2.91
CAS 2 -2	2 STR	BROWN	10	0.416	0.307	2.65
CAS 3 -2	3 STR	WHITE	9	0.377	0.284	2.53
CAT 4 -2	4 STR	GRAY	8 OR 346	0.340	0.248	2.41
CAT 6 -6	6 STR	BLUE	7 OR 374	0.292	0.195	2.41

- ETP copper alloy c11000 per ASTM SPEC B188 copper tube
- Electro tinned plated

