

**Copper Forged Lugs**

- Electrolytic high conductivity copper
- With/without electro tin plating



Product Ref.	Conductor Size mm <sup>2</sup>	Stud Hole	Dimensions mm			
			E	I	O	L1
CFC-16/8	16	M 8	5.5	8.5	36.0	20
CFC-16/10		M 10				
CFC-16/12		M 12				
CFC-25/8	25	M 8	7.0	10.0	38.5	20
CFC-25/10		M 10				24
CFC-25/12		M 12				20
CFC-35/8	35	M 8	8.2	12.5	40.0	25
CFC-35/10		M 10				
CFC-35/12		M 12				
CFC-50/8	50	M 8	10.0	14.5	48.0	25
CFC-50/10		M 10				
CFC-50/12		M 12				
CFC-70/10	70	M 10	11.5	16.5	49.0	25
CFC-70/12		M 12				30
CFC-70/16		M 16				
CFC-95/10	95	M 10	13.5	19.0	56.0	25
CFC-95/12		M 12				
CFC-120/12	120	M 12	15.5	21.0	62.0	30
CFC-120/16		M 16				
CFC-150/12	150	M 12	17.0	23.5	63.0	30
CFC-150/16		M 16				
CFC-185/12	185	M 12	19.0	25.5	69.0	30
CFC-185/16		M 16				
CFC-240/12	240	M 12	21.5	29.0	74.0	38
CFC-240/16		M 16				
CFC-240/20		M 20				
CFC-300/16	300	M 16	24.5	32.0	85.0	38
CFC-300/20		M 20				
CFC-400/16	400	M 16	26.0	38.5	106.0	38
CFC-400/20		M 20				
CFC-500/16	500	M 16	29.0	42.0	106.0	38
CFC-500/20		M 20				