


**Stainless Steel
Tubular Cable Lugs**

For food-industry compliant

- Material stainless steel V2a
- Heat resistant up to 400°C
- Ring type




Product Ref.	Conductor Size mm ²	Stud Hole				
		E	I	O	L	B
CSST	0.5-1	M 4	1.6	3.2	13.0	6.0
CSST		M 5	1.6	3.2	14.0	6.0
CSST	1.5-2.5	M 4	3.0	5.0	17.0	8.0
CSST		M 5	3.0	5.0	17.0	8.0
CSST		M 6	3.0	5.0	19.0	8.0v
CSST	4 - 6	M 4	4.0	6.0	18.0	9.0
CSST		M 5	4.0	6.0	19.0	9.0
CSST		M 6	4.0	6.0	19.0	9.0
CSST	10	M 5	5.0	8.0	22.0	10.0
CSST		M 6	5.0	8.0	22.0	10.0
CSST		M 8	5.0	8.0	25.0	10.0
CSST	16	M 5	6.0	8.0	28.0	13.0
CSST		M 6	6.0	8.0	28.0	13.0
CSST		M 8	6.0	8.0	29.0	13.0
CSST	25	M 6	7.0	10.0	30.0	15.0
CSST		M 8	7.0	10.0	32.0	15.0
CSST	35	M 6	9.0	12.0	32.0	17.0
CSST		M 8	9.0	12.0	35.0	17.0
CSST	50	M 6	10.0	14.0	37.0	19.0
CSST		M 8	10.0	14.0	37.0	19.0
CSST		M 10	10.0	14.0	39.0	19.0
CSST		M 12	10.0	14.0	43.0	19.0
CSST	70	M 8	12.0	16.0	43.0	21.0
CSST		M 10	12.0	16.0	44.0	21.0
CSST		M 12	12.0	16.0	46.0	21.0
CSST		M 16	12.0	16.0	46.0	21.0
CSST	95	M 8	14.0	18.0	48.0	25.0
CSST		M 10	14.0	18.0	48.0	25.0
CSST		M 12	14.0	18.0	49.0	25.0

Acid and rust-resistant stainless steel
tubular cable lugs and connectors, heat resistance to 400°C

**Stainless Steel
Butt Connectors**

- Material stainless steel V2a
- Heat resistant up to 400°C
- Ring type



Product Ref.	Conductor Size mm ²	Stud Hole		
		I	O	L
CSSC	0.5-1	1.6	3.2	25.0
CSSC	1.5-2.5	3.0	5.0	25.0
CSSC	4 - 6	4.0	6.0	25.0
CSSC	10	5.0	8.0	25.0
CSSC	16	6.0	8.0	30.0
CSSC	25	7.0	10.0	35.0
CSSC	35	9.0	12.0	40.0
CSSC	50	10.0	14.0	45.0
CSSC	70	12.0	16.0	50.0
CSSC	95	14.0	18.0	55.0