


**Nickel
Tubular Cable Lugs**



| Product Ref. | Conductor Size mm ² | Stud Hole | | | | | | |
|--------------|--------------------------------|-----------|------|------|------|------|------|------|
| | | | I | O | L | E | B | |
| CNPT | 0.5-1 | M 4 | 1.6 | 3.2 | 13.0 | 4.3 | 6.0 | |
| CNPT | | M 5 | 1.6 | 3.2 | 14.0 | 5.3 | 6.0 | |
| CNPT | 1.5-2.5 | M 4 | 2.3 | 3.9 | 13.0 | 4.3 | 6.0 | |
| CNPT | | M 5 | 2.3 | 3.9 | 14.0 | 5.5 | 6.0 | |
| CNPT | | M 6 | 2.3 | 3.9 | 16.0 | 6.5 | 6.0 | |
| CNPT | 4 - 6 | M 4 | 3.6 | 5.6 | 18.0 | 4.3 | 9.0 | |
| CNPT | | M 5 | 3.6 | 5.6 | 19.0 | 5.5 | 9.0 | |
| CNPT | | M 6 | 3.6 | 5.6 | 19.0 | 6.5 | 9.0 | |
| CNPT | | 10 | M 5 | 4.5 | 6.5 | 21.0 | 5.5 | 10.0 |
| CNPT | | | M 6 | 4.5 | 6.5 | 22.0 | 6.5 | 10.0 |
| CNPT | | 16 | M 5 | 5.5 | 7.5 | 26.0 | 5.5 | 13.0 |
| CNPT | M 6 | | 5.5 | 7.5 | 27.0 | 6.5 | 13.0 | |
| CNPT | M 8 | | 5.5 | 7.5 | 29.0 | 8.5 | 13.0 | |
| CNPT | 25 | | M 6 | 7.0 | 10.0 | 30.0 | 6.5 | 15.0 |
| CNPT | | M 8 | 7.0 | 10.0 | 32.0 | 8.5 | 15.0 | |
| CNPT | | M 6 | 8.5 | 12.0 | 32.0 | 6.5 | 17.0 | |
| CNPT | 35 | M 8 | 8.5 | 12.0 | 34.0 | 8.5 | 17.0 | |
| CNPT | | M 8 | 10.0 | 14.0 | 37.0 | 8.5 | 19.0 | |
| CNPT | 50 | M 8 | 10.0 | 14.0 | 37.0 | 8.5 | 19.0 | |
| CNPT | | M 10 | 10.0 | 14.0 | 39.0 | 10.5 | 19.0 | |
| CNPT | 70 | M 10 | 12.0 | 16.5 | 44.0 | 10.5 | 21.0 | |
| CNPT | | M 12 | 12.0 | 16.5 | 46.0 | 13.0 | 21.0 | |
| CNPT | 95 | M 10 | 13.5 | 18.0 | 48.0 | 10.5 | 25.0 | |
| CNPT | | M 12 | 13.5 | 18.0 | 49.0 | 13.0 | 25.0 | |

- Material high grade nickel
- Heat resistant up to 650 °C
- Ring type

**Nickel tubular cable lugs and connectors,
heat resistant to 650 °C.**

- Most suitable for use in furnaces.
- It retain there conductivity and malfunctions are excluded.
- Reliable electrical connection in aggressive environments.