

T - Connectors


- Standard type
- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Cross Section mm ²	I	O	L	L1
CTC 1.5	1.5	1.8	3.3	30	12
CTC 2.5	2.5	2.3	4.2	30	12
CTC 4	4	3.0	5.0	30	12
CTC 6	6	4.0	6.0	35	14
CTC 10	10	4.5	7.0	35	14
CTC 16	16	5.5	8.5	50	21
CTC 25	25	7.0	10.0	55	23
CTC 35	35	8.5	12.0	70	30
CTC 50	50	10.0	14.0	80	34
CTC 70	70	12.0	16.5	85	35
CTC 95	95	13.5	18.0	90	36
CTC 120	120	15.0	19.5	95	38
CTC 150	150	16.5	21.0	110	44
CTC 185	185	19.0	24.0	115	45
CTC 240	240	21.0	26.0	130	52

T - Connectors

- Special type, for solid conductor
- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Cross Section mm ²	I	O	L	L1
CTCS 1.5	1.5	1.9	3.9	30	12
CTCS 2.5	2.5	1.9	3.9	30	12
CTCS 4	4	2.4	4.4	30	12
CTCS 6	6	3.0	5.0	30	12
CTCS 10	10	4.0	6.0	35	14
CTCS 16	16	5.0	8.0	35	14
CTCS 25	25	6.2	10.0	50	21
CTCS 35	35	7.0	10.0	55	23
CTCS 50	50	8.5	12.0	76	32