


Aluminum Through Connectors

- Electrolytic high conductivity aluminum



Product Ref	Dimensions mm	
	I	L
CABC / CATC 16	5.5	90.5
CABC / CATC 25	6.5	90.5
CABC / CATC 35	8	90.5
CABC / CATC 50	9	106.5
CABC / CATC 70	11	106.5
CABC / CATC 95	12.5	106.5
CABC / CATC 120	13.7	133
CABC / CATC 150	15.5	133
CABC / CATC 185	17	143.5
CABC / CATC 240	19.5	143.5
CABC / CATC 300	22.5	144.5

Aluminum Reducer Compression Connector Non Tension

- Electrolytic high conductivity aluminum



Product Ref.	Dimensions mm			
	I1	I2	L	O
CARC 50-25	9	6.5	106.5	20
CARC 50-35	9	8	106.5	20
CARC 70-35	11	8	106.5	20
CARC 70-50	11	9	106.5	20
CARC 95-50	12.5	9	109.4	20
CARC 95-70	12.5	11	106.5	20
CARC 120-70	13.7	11	133	25
CARC 120-95	13.7	12.5	133	25
CARC 150-70	15.5	11	133	25
CARC 150-95	15.5	12.5	134.4	25
CARC 150-120	15.5	13.7	133	25
CARC 185-120	17	13.7	143.5	32
CARC 185-150	17	15.5	143.5	32
CARC 240-150	19.5	15.5	145.6	32
CARC 240-185	19.5	17	143.5	32
CARC 300-185	22.5	17	144.5	34
CARC 300-240	22.5	19.5	144.5	34