


**Bi-Metallic Lugs**

For cables with aluminium, compact round and pre-rounded sector shaped conductors. Al. barrel friction welded to solid copper palm



Product Ref	Dimension mm				
	E	W	I	O	L
CBL 16	13/17	35	5.5	12	125
CBL 25	13/17	35	6.5	12	125
CBL 35	13/17	35	8.5	14	125
CBL 50	13/17	35	9.5	16	125
CBL 70	13/17	35	11.0	18	125
CBL 95	13/17	35	12.5	22	125
CBL 120	13/17	35	13.7	23	135
CBL 150	13/17	35	15.5	25	135
CBL 185	13/17	35	17.0	28	135
CBL 240	13/17	35	19.5	32	135
CBL 300	13/17	35	22.5	34	145
CBL 400	13/17	35	25.0	38	155
CBL 500	*	60x60	28.5	44	200
CBL 630	*	60x60	31.7	44	200
CBL 800	**	80x80	35.7	50	260
CBL 1000	**	80x80	42.0	58	260

Note: Dimension 'O' can be to local standards/Customer Specification  
\* 1-hole to customer specification  
\*\* 2-holes/4-holes to customer specification

**Bi Metallic Connectors**



Compression Joints Aluminum with Copper Connecting Pin



Product Ref.	Dimension mm		
	I	O	L
CBC 16	5.5	8	82
CBC 25	6.5	8	82
CBC 35	8.0	8	82
CBC 50	9	12	97
CBC 70	11	12	97
CBC 95	12.5	12	97
CBC 120	13.7	14	125
CBC 150	15.5	14	125
CBC 185	17	14	125
CBC 240	19.5	14	125