


**Cable Terminal Ends
Pin Type**


- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm ²	Stud Hole	Dimensions mm								
			E	I	O	W	T	B	G+H	L	TYPE
D-CPT-9	1.5	--	1.6	3.2	1.9	0.8	5	10	17	I	
D-CPT-1	2.5	--	2.3	3.9	1.9	0.8	5	10	17	I	
D-CPT-2	2.5	--	2.3	3.9	3.1	0.8	5	10	17	II	
D-CPT-3	4	--	2.9	4.9	2.7	1	6	10	20	I	
D-CPT-5	6	--	3.6	5.6	2.7	1	6	10	20	I	
D-CPT-7	10	2.4	4.5	6.7	4.3	1.1	8	12	22	III	
D-CPT-8	16	2.6	5.8	8.2	5.5	1.2	10	13	23	III	

**Cable Terminal Ends
Pin Type Insulated**

- Electrolytic high conductivity copper
Electro tinned plated
PVC Insulation



Product Ref.	Conductor Size mm ²	Stud Hole	Dimensions mm									
			E	I	O	W	T	B	G+H	L	OI	LI
D-CIPT-17	1.5	--	1.6	3.2	1.9	0.8	5	10	17	4.8	10	I
D-CIPT-18	2.5	--	2.3	3.9	1.9	0.8	5	10	17	5.5	10	I
D-CIPT-19	2.5	--	2.3	3.9	3.1	0.8	5	10	17	5.5	10	II
D-CIPT-20	4	--	2.9	4.9	2.7	1	6	10	20	7.1	14	I
D-CIPT-22	6	--	3.6	5.6	2.7	1	6	10	20	7.1	14	I



Cable Terminal Ends:
Pin Type Reinforce Insulated
Tinned Copper

Also available Range in Reinforce