


**Tubular Cable Lugs**


Tinned Copper



Product Ref.	Conductor Size mm <sup>2</sup>	Stud Hole E	Dimensions mm									
			I	O	W	T	B	K	C1	C2	L	
CTD-05	2,5	5,2	2,0	3,7	9	1,0	7	3	5	5	20	
CTD-06	4	6,5	3,1	4,8	11	1,0	7	3	6	6	22	
CTD-07	6	6,5	3,8	5,5	11	1,0	9	3	6	6	24	
CTD-08	10	6,5	4,4	6,2	11	1,3	9	3	6	6	24	
CTD-09	16	6,5	5,3	7,1	11	1,6	12	4	8	6	30	
CTD-10	25	6,5	7,0	9,0	13	2,0	12	5	12	8	37	
CTD-11	35	6,5	8,0	10,0	15	2,0	12	5	12	8	37	
CTD-12	35	8,2	8,0	10,0	15	2,0	12	5	12	8	37	
CTD-13	50	6,5	9,2	11,2	16	2,0	16	8	12	9	45	
CTD-14	50	8,2	9,2	11,2	16	2,0	16	8	12	9	45	
CTD-15	50	10,2	9,2	11,2	16	2,0	16	8	12	9	45	
CTD-16	70	8,2	11,5	13,8	20	2,3	18	10	15	13	56	
CTD-17	70	10,2	11,5	13,8	20	2,3	18	10	15	13	56	
CTD-18	70	12,7	11,5	13,8	20	2,3	18	10	15	13	56	
CTD-19	95	10,2	12,8	15,6	23	2,8	20	10	15	13	58	
CTD-20	95	12,7	12,8	15,6	23	2,8	20	10	15	13	58	
CTD-21	120	10,2	14,8	17,8	26	3,0	22	10	16	14	62	
CTD-22	120	12,7	14,8	17,8	26	3,0	22	10	16	14	62	
CTD-23	120	16,2	14,8	17,8	26	3,0	22	10	16	14	62	
CTD-24	150	10,2	16,0	19,6	28	3,6	26	11	18	15	70	
CTD-25	150	12,7	16,0	19,6	28	3,6	26	11	18	15	70	
CTD-26	150	16,2	16,0	19,6	28	3,6	26	11	18	15	70	
CTD-27	185	12,7	18,0	22,0	32	4,0	28	13	21	21	83	
CTD-28	185	16,2	18,0	22,0	32	4,0	28	13	21	21	83	
CTD-231	225	16,2	20,0	24,0	35	4,0	32	15	24	24	95	
CTD-29	240	16,2	22,0	26,0	35	4,0	34	15	24	24	97	
CTD-30	240	20,3	22,0	26,0	38	4,0	34	15	24	24	97	
CTD-31	300	16,2	24,0	28,7	38	4,7	36	16	25	25	103	
CTD-32	300	20,3	24,0	28,7	42	4,7	36	16	25	25	103	
CTD-33	400	20,3	28,0	33,2	42	5,2	44	18	27	27	116	
CTD-34	500	20,3	30,0	36,0	53	6,0	48	18	27	27	120	
CTD-35	630	20,3	35,0	41,5	61	6,5	53	20	33	31	137	
CTD-062	800	-	39,0	46,3	67	7,3	68	25	38	37	165	
CTD-076	1000	-	43,0	53,8	76	10,8	90	30	45	45	210	

**Tubular Cable Lugs Heavy Duty**

Tinned Copper



Product Ref.	Conductor Size mm <sup>2</sup>	Stud Hole E	Dimensions mm									
			I	O	W	T	B	K	C1	C2	L	
CTD-282	25	8,2	7,0	9,0	13	2,0	7	3	5	5	20	
CTD-283	35	8,2	8,0	10,6	15	2,6	7	3	6	6	22	
CTD-284	50	8,2	9,2	12,2	17	3,0	9	3	6	6	24	
CTD-285	70	10,2	11,5	15,0	20	3,5	9	3	6	6	24	
CTD-286	95	12,7	12,8	17,0	24	4,2	12	4	8	6	30	
CTD-287	120	12,7	14,8	19,6	28	4,8	12	5	12	8	37	
CTD-288	150	12,7	16,0	21,2	30	5,2	62	5	12	8	37	
CTD-289	185	12,7	18,0	24,0	34	6,0	43	5	12	8	37	
CTD-290	240	16,2	22,0	28,0	40	6,0	50	8	12	9	45	