


**Copper Reducer Type  
Terminal End**

For Solderless Crimping to Aluminum Conductor  
Suitable for Fuse Units and ICTP Switches

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm <sup>2</sup>	Dimensions mm							
		I	O	W	W1	B	K	G+H	L
CWPC-1	2.5	2.5	4.7	4.5	4.0	6	4	10	20
CWPC-7	2.5	2.5	4.7	3.8	3.3	6	4	10	20
CWPC-15	4	2.8	4.7	4.5	4.0	6	4	10	20
CWPC-16	4	2.8	4.7	3.8	3.3	6	4	10	20
CWPC-17	6	3.1	4.7	4.5	4.0	6	4	10	20
CWPC-18	6	3.1	4.7	3.8	3.3	6	4	10	20
CWPC-19	10	3.8	5.5	4.5	4.0	9	4	10	23
CWPC-20	10	3.8	5.5	3.8	3.3	9	4	10	23
CWPC-21	10	4.4	6.2	4.5	4.0	9	4	10	23
CWPC-22	10	4.4	6.2	3.8	3.3	9	4	10	23
CWPC-23	16	5.3	7.1	6.0	5.5	12	5	15	32
CWPC-24	16	5.3	7.1	6.0	5.5	12	5	20	37
CWPC-2	16	5.3	7.1	3.8	3.3	12	5	13	30
CWPC-25	25	7.0	9.0	6.0	5.5	12	5	15	32
CWPC-3	25	7.0	9.0	7.5	6.5	12	5	20	37
CWPC-4	35	8.0	10.0	7.5	6.5	12	5	20	37
CWPC-26	50	9.2	11.2	7.5	6.5	16	5	20	41
CWPC-5	50	10.4	14.0	14	13.0	18	7	24	49
CWPC-27	70	11.5	13.8	7.5	6.5	18	5	20	43
CWPC-6	70	11.5	13.8	11.5	10.5	18	5	25	48
CWPC-28	70	11.5	13.8	11.5	10.5	18	5	32	55
CWPC-29	95	12.8	15.6	11.5	10.5	20	6	25	51
CWPC-6	95	12.8	15.6	15.6	14.0	20	6	27	53
CWPC-31	95	12.8	15.6	7.5	6.5	20	6	22	48
CWPC-32	95	12.8	15.6	12.8	11.8	20	6	32	58
CWPC-33	120	14.8	17.8	11.5	10.5	22	6	25	53
CWPC-34	120	14.8	17.8	7.5	6.5	22	6	22	50
CWPC-35	120	14.8	17.8	11.5	10.5	22	6	32	60
CWPC-36	120	14.8	17.8	15.6	14.0	22	6	32	60
CWPC-10	150	16.0	19.6	15.6	14.0	26	6	32	64
CWPC-37	150	16.0	19.6	11.5	10.5	26	6	32	64
CWPC-30	185	18.0	22.0	15.6	14.0	32	6	32	70
CWPC-38	185	18.0	22.0	11.5	10.5	32	6	32	70
CWPC-39	225	20.0	26.0	15.6	14.0	38	8	32	78
CWPC-46	225	20.0	26.0	21.0	18.0	38	8	42	88
CWPC-42	225	20.0	26.0	16.0	15.0	38	8	42	88
CWPC-44	240	22.0	26.0	16.0	15.0	38	8	42	88
CWPC-43	240	22.0	26.0	15.6	14.0	38	8	32	78
CWPC-45	300	24.0	28.7	16.0	15.0	42	8	42	92
CWPC-47	300	24.0	28.7	15.6	14.0	42	8	32	82