



Copper Ring Tongue Fork
Terminal End : Insulated

For Solderless Crimping to Copper/Aluminum Conductor

- Electrolytic high conductivity copper
- Electro tinned plated



Also available
Range in Reinforce

Product Ref.	Conductor Size mm ²	Stud Hole E	Dimensions mm											
			I	O	O1	W	T	B	K	C2	C1	L-3	L-1	L
CIFT-7873	1.5	3.1	1.6	3.2	4.8	6.0	0.8	5	2	4	3	16.0	10	14
CIFT-7874	1.5	3.6	1.6	3.2	4.8	6.0	0.8	5	2	4	3	16.0	10	14
CIFT-7875	1.5	3.1	1.6	3.2	4.8	6.8	0.8	5	-	4.6	3.4	14.6	10	13
CIFT-7876	1.5	3.6	1.6	3.2	4.8	6.8	0.8	5	-	4.6	3.4	14.6	10	13
CIFT-7877	1.5	4.1	1.6	3.2	4.8	7.0	0.8	5	1	5	3.5	16.0	10	14
CIFT-7878	1.5	4.1	1.6	3.2	4.8	8.0	0.8	5	2	5	4	17.0	10	16
CIFT-7879	1.5	5.1	1.6	3.2	4.8	10.0	0.8	5	2	6	5	18.0	10	18
CIFT-7880	1.5	6.1	1.6	3.2	4.8	10.0	0.8	5	2	6	5	18.0	10	18
CIFT-7881	2.5	3.1	2.3	3.9	5.5	6.5	0.8	5	1	3.5	3.2	14.5	10	12.7
CIFT-7882	2.5	3.6	2.3	3.9	5.5	6.5	0.8	5	1	3.5	3.2	14.5	10	12.7
CIFT-7883	2.5	4.1	2.3	3.9	5.5	8.0	0.8	5	2	5	4	17.0	10	16
CIFT-7884	2.5	5.1	2.3	3.9	5.5	10.0	0.8	5	1	7	5	18.0	10	18
CIFT-7885	2.5	6.1	2.3	3.9	5.5	10.0	0.8	5	1	7	5	18.0	10	18
CIFT-7886	4-6	4.1	3.5	5.5	7.1	8.0	1.0	6	2	5	4	21.0	14	17
CIFT-7887	4-6	4.1	3.5	5.5	7.1	10.0	1.0	6	3	5	5	22.0	14	19
CIFT-7888	4-6	5.1	3.5	5.5	7.1	10.0	1.0	6	3	5	5	22.0	14	19
CIFT-7889	4-6	5.1	3.5	5.5	7.1	12.0	1.0	6	3	7	6	24.0	14	22
CIFT-7890	4-6	6.1	3.5	5.5	7.1	12.0	1.0	6	3	7	6	24.0	14	22
CIFT-7891	10	4.1	4.3	6.3	7.9	10.0	1.0	8	2	7	5	25.0	16	22
CIFT-7892	10	5.1	4.3	6.3	7.9	10.0	1.0	8	2	7	5	25.0	16	22
CIFT-7893	10	6.1	4.3	6.3	7.9	12.0	1.0	8	2	7	6	25.0	16	23
CIFT-7894	10	8.1	4.3	6.3	7.9	16.0	1.0	8	4	7	8	27.0	16	27
CIFT-7895	16	5.1	5.6	8.0	10.0	10.0	1.2	10	3	6	5	29.0	20	24
CIFT-7896	16	6.1	5.6	8.0	10.0	12.0	1.2	10	4	6	6	30.0	20	26
CIFT-7897	16	8.1	5.6	8.0	10.0	16.0	1.2	10	4	8	8	32.0	20	30
CIFT-7898	16	8.1	5.6	8.0	10.0	18.0	1.2	10	4	10	9	34.0	20	33