


Copper Fork Hook Terminal End : Insulated

For Solderless Crimping to Copper/Aluminum Conductor

- Electrolytic high conductivity copper
- Electro tinned plated

Also available
Range in Reinforce



| Product Ref. | Conductor Size mm ² | Stud Hole E | Dimensions mm | | | | | | | | | | | |
|--------------|--------------------------------|-------------|---------------|-----|-----|------|-----|---|---|-----|-----|------|-----|------|
| | | | I | O | O1 | W | T | B | K | C2 | P | L-3 | L-1 | L |
| CIFH-7943 | 0.75 | 2.3 | 0.9 | 1.9 | 3.2 | 4.6 | 0.5 | 3 | - | 5 | 1.2 | 13.0 | 8 | 11 |
| CIFH-7944 | 1.5 | 2.3 | 1.6 | 3.2 | 4.8 | 6.0 | 0.8 | 5 | - | 5.2 | 1.0 | 20.2 | 10 | 13 |
| CIFH-7945 | 1.5 | 2.3 | 1.6 | 3.2 | 4.8 | 4.6 | 0.8 | 5 | - | 5.2 | 1.0 | 20.2 | 10 | 13 |
| CIFH-7946 | 1.5 | 4.1 | 1.7 | 3.3 | 4.8 | 7.5 | 0.8 | 5 | - | 6.5 | 2.4 | 21.5 | 10 | 15 |
| CIFH-7947 | 1.5 | 3.6 | 1.6 | 3.2 | 4.8 | 6.8 | 0.8 | 5 | 2 | 3 | 1.6 | 20.0 | 10 | 15 |
| CIFH-7948 | 1.5 | 5.1 | 1.6 | 3.2 | 4.8 | 8.0 | 0.8 | 5 | 2 | 5 | 1.6 | 22.0 | 10 | 18 |
| CIFH-7949 | 1.5 | 6.3 | 1.6 | 3.2 | 4.8 | 12.0 | 0.8 | 5 | 3 | 5 | 1.6 | 23.0 | 10 | 19 |
| CIFH-7950 | 1.5 | 8.1 | 1.6 | 3.2 | 4.8 | 12.0 | 0.8 | 5 | 3 | 5 | 1.6 | 23.0 | 10 | 19 |
| CIFH-7951 | 2.5 | 3.6 | 2.3 | 3.9 | 5.5 | 6.5 | 0.8 | 5 | 2 | 3 | 1.6 | 20.0 | 10 | 15 |
| CIFH-7952 | 2.5 | 4.1 | 2.3 | 3.9 | 5.5 | 7.7 | 0.8 | 5 | 2 | 3 | 1.6 | 20.0 | 10 | 16 |
| CIFH-7953 | 2.5 | 5.1 | 2.3 | 3.9 | 5.5 | 10.0 | 0.8 | 5 | 2 | 5 | 1.6 | 22.0 | 10 | 18 |
| CIFH-7954 | 2.5 | 6.3 | 2.3 | 3.9 | 5.5 | 12.0 | 0.8 | 5 | 3 | 5 | 1.6 | 23.0 | 10 | 19 |
| CIFH-7955 | 2.5 | 8.1 | 2.3 | 3.9 | 5.5 | 12.0 | 0.8 | 5 | 3 | 5 | 1.6 | 23.0 | 10 | 19 |
| CIFH-7956 | 4.0 | 4.1 | 3.1 | 5.5 | 7.1 | 10.0 | 1.2 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7957 | 4.0 | 5.1 | 3.1 | 5.5 | 7.1 | 10.0 | 1.2 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7958 | 4.0 | 6.3 | 3.1 | 5.5 | 7.1 | 12.0 | 1.2 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7959 | 4.0 | 8.1 | 3.1 | 5.5 | 7.1 | 12.0 | 1.2 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7960 | 4-6 | 4.1 | 3.5 | 5.5 | 7.1 | 10.0 | 1.0 | 6 | 3 | 3 | 2.0 | 28.0 | 14 | 18 |
| CIFH-7961 | 4-6 | 5.1 | 3.5 | 5.5 | 7.1 | 10.0 | 1.0 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7962 | 4-6 | 5.1 | 3.5 | 5.5 | 7.1 | 12.0 | 1.0 | 6 | 3 | 5 | 2.0 | 30.0 | 14 | 20 |
| CIFH-7963 | 4-6 | 4.1 | 3.5 | 5.5 | 7.1 | 8.0 | 1.0 | 6 | 2 | 5 | 2.0 | 29.0 | 14 | 17 |
| CIFH-7964 | 4-6 | 5.1 | 3.5 | 5.5 | 7.1 | 8.0 | 1.0 | 6 | 2 | 5 | 2.0 | 29.0 | 14 | 17 |
| CIFH-7965 | 6.0 | 4.1 | 3.9 | 5.9 | 7.1 | 10.0 | 1.0 | 6 | 4 | 3 | 2.0 | - | 14 | 19 |
| CIFH-7966 | 6.0 | 4.1 | 3.9 | 5.9 | 7.1 | 10.0 | 1.0 | 6 | - | 8.5 | 1.5 | - | 14 | 20.5 |