


## Compression Type Aluminum Tubular Connectors

- Electrolytic high conductivity aluminum
- Electro tinned plated



Product Ref.	Conductor Size mm <sup>2</sup>	Dimensions mm		
		I	O	L
CAI-145	2.5	2.0	5.5	16
CAI-6	2.5	2.6	5.5	16
CAI-5	4.0	2.9	5.5	16
CAI-13	6.0	3.5	5.5	16
CAI-146	10.0	3.8	6.2	20
CAI-14	10.0	4.4	7.4	20
CAI-4	16.0	5.4	8.3	26
CAI-3	25.0	7.0	9.7	35
CAI-2	35.0	8.0	10.8	40
CAI-12	50.0	9.3	13.0	45
CAI-1	70.0	11.6	16.0	55
CAI-15	95.0	12.9	17.1	60
CAI-9	120.0	15.0	19.6	65
CAI-10	150.0	16.5	21.2	70
CAI-11	185.0	18.5	24.0	75
CAI-147	225.0	21.0	27.0	85
CAI-16	240.0	22.0	28.6	90
CAI-17	300.0	25.0	32.0	100
CAI-18	400.0	29.0	37.5	115
CAI-19	500.0	31.0	41.0	125
CAI-20	625.0	36.0	46.0	140
CAI-148	800.0	39.0	51.0	160
CAI-149	1000.0	43.5	57.0	210