


**Tubular Cable Lugs
Standard Type**

- Electrolytic high conductivity copper
- Electro-finned plated
- With/without inspection hole



Product Ref.	Conductor Size mm²	Stud Hole	Dimensions mm								
			E	I	B	W	E	O	C1	C2	L
CS 95-8	95	M 8	13.5	25	26	8.5	18	12	12	48	
CS 95-10	95	M 10			26	10.5		12	12	48	
CS 95-12	95	M 12			26	13		13	13	49	
CS 95-14	95	M 14			26	15		14.5	14.5	51	
CS 95-16	95	M 16			28	17		16	16	54	
CS 95-20	95	M 20			36	21		22	22	60	
CS 120-8	120	M 8	15	26	28	8.5	19.5	14	14	51	
CS 120-10	120	M 10			28	10.5		14	14	51	
CS 120-12	120	M 12			28	13		14	14	51	
CS 120-14	120	M 14			28	15		15	15	52	
CS 120-16	120	M 16			30	17		16	16	54	
CS 120-20	120	M 20			36	21		22	22	63	
CS 150-8	150	M 8	16.5	30	31	8.5	21	14	14	56	
CS 150-10	150	M 10			31	10.5		14	14	56	
CS 150-12	150	M 12			31	13		15	15	57	
CS 150-14	150	M 14			31	15		15	15	57	
CS 150-16	150	M 16			31	17		16	16	58	
CS 150-20	150	M 20			36	21		22	22	66	
CS 185-10	185	M 10	19	30	35	10.5	24	18	18	65	
CS 185-12	185	M 12			35	13		18	18	65	
CS 185-14	185	M 14			35	15		18	18	65	
CS 185-16	185	M 16			35	17		18	18	65	
CS 185-20	185	M 20			39	21		22	22	69	
CS 240-10	240	M 10	21	35	39	10.5	26	21.5	19	72	
CS 240-12	240	M 12			39	13		21.5	19	72	
CS 240-14	240	M 14			39	15		21.5	19	72	
CS 240-16	240	M 16			39	17		21.5	19	72	
CS 240-20	240	M 20			39	21		21.5	19	72	
CS 300-12	300	M 12	23.5	44	43	13	29.5	24	24	87	
CS 300-14	300	M 14			43	15		24	24	87	
CS 300-16	300	M 16			43	17		24	24	87	
CS 300-20	300	M 20			43	21		24	24	87	
CS 400-12	400	M 12	27	44	49	13	34	24	24	90	
CS 400-14	400	M 14			49	15		24	24	90	
CS 400-16	400	M 16			49	17		24	24	90	
CS 400-20	400	M 20			49	21		24	24	90	


CS - 45

CS - 90

CS - EE