

Copper Tubular End Sealing Ferrules DIN 46228

For Solderless Crimping to Copper/Aluminum Conductors

- Electrolytic high conductivity copper
- Electro tinned plated



Product Ref.	Conductor Size mm²	Dimensions mm					
		I	O	O-1	K	R	L
CSF-508	0.5	1.0-1.1	1.4-1.5	2.1	0.7	0.8	6
CSF-509	0.75	1.4-1.5	1.8-1.9	2.5	0.7	0.8	6
CSF-510	1.0	1.6-1.7	2.0-2.1	2.7	0.7	0.8	6
CSF-511	1.0	1.8-1.9	2.0-2.1	2.7	0.7	0.8	10
CSF-512	1.5	2.3-2.4	2.2-2.3	2.9	1.0	1.2	7
CSF-513	1.5	2.3-2.4	2.2-2.3	2.9	1.0	1.2	10
CSF-514	2.5	2.8-2.9	2.7-2.8	3.5	1.0	1.2	7
CSF-515	2.5	3.7-3.8	2.7-2.8	3.5	1.0	1.2	12
CSF-516	4.0	3.7-3.8	3.2-3.3	4.0	1.0	1.2	9
CSF-517	4.0	4.6-4.7	3.2-3.3	4.0	1.0	1.2	12
CSF-518	6.0	4.6-4.7	4.1-4.2	4.8	1.0	1.2	10
CSF-519	6.0	4.6-4.7	4.1-4.2	4.8	1.0	1.2	12
CSF-520	6.0	5.9-6.0	4.1-4.2	4.8	1.0	1.2	15
CSF-521	10.0	4.6-4.7	5.0-5.1	5.8	1.2	1.2	12
CSF-522	10.0	4.6-4.7	5.0-5.1	5.8	1.2	1.2	15
CSF-523	10.0	4.6-4.7	5.0-5.1	5.8	1.2	1.2	18
CSF-524	16.0	5.9-6.0	6.3-6.4	7.5	1.5	1.6	12
CSF-525	16.0	5.9-6.0	6.3-6.4	7.5	1.5	1.6	15
CSF-526	16.0	5.9-6.0	6.3-6.4	7.5	1.5	1.6	18

Copper Tubular End Sealing Ferrules

For Solderless Crimping to Copper/Aluminum Conductors



Product Ref.	Conductor Size mm²	Dimensions mm		
		I	O	L
CI-459	1.5	1.8	2.6	10
CI-466	2.5	2.4	3.2	10
CI-495	4	2.7	3.5	15
CI-568	6	3.5	4.3	15
CI-569	10	4.4	5.2	15
CI-570	16	5.3	6.1	18
CI-571	25	7.0	7.8	18
CI-500	35	8.0	8.8	18
CI-572	50	9.3	10.1	21
CI-497	70	11.5	12.3	21
CI-573	95	12.8	13.6	21
CI-574	120	14.8	15.6	21
CI-575	150	16.0	16.8	21
CI-496	185	18.0	18.8	21